

## Advanced Color Gigabit IP Business Phone

The ZIP 47GE combines a hi-resolution color display and dual Gigabit Ethernet ports in a feature-rich IP phone that's ideal for busy executives and heavy phone users.

Functions and contacts may be accessed quickly via 27 programmable soft keys. A dedicated headset port and Electronic Hook Switch support offer enhanced usability for wired and wireless headset users. The optional ZIP 450M Expansion Module supports additional programmable keys.

The ZIP 47GE is fully compatible with Zultys' ZAC Unified Communication applications, allowing users to manage calls and messages directly from their computer.

Like all Zultys phones, the ZIP 47GE utilizes the Session Initiation Protocol (SIP) open standard and is managed from the Zultys MX Administrator application for rapid deployment and the industry's lowest total cost of ownership.



## Key Features and Benefits:

### Vivid Color Display & Gigabit Ethernet

The 4.3" hi-resolution 480x272 pixel color display of the ZIP 47GE provides detailed call information accompanied by dynamic icons to minimize training requirements and maximize usability. Ten LCD-labeled buttons support up to 27 programmable keys (three pages of nine keys). The key alert feature ensures that users are instantly alerted to Busy Lamp Field (BLF) and new call events. Four context-sensitive soft keys below the display make conferencing, transfer, and other operations a breeze.

### Expansion Module and Wireless Headset Support (EHS)

The ZIP 47GE may be combined with up to three ZIP 450M Color Expansion Modules to facilitate up to 180 additional LCD-labeled programmable keys, making it ideal for operators and receptionists. Staff requiring mobility around the office will appreciate the convenience of the Electronic Hook Switch control when the ZIP 47GE is combined with a compatible Wireless Headset and EHS 4xi adapter. The ZIP 47GE may also be used with a compatible Bluetooth headset via a built-in Bluetooth adapter.

### Remarkable Audio

A full-duplex speakerphone with acoustic echo cancellation combined with high-quality wideband HD speaker, microphone, and handset components ensure that conversations are always loud and clear and minimize fatigue for heavy phone users.

### Simplified Deployment & SIP Open Standard

From initial deployment and configuration to future enhancements and upgrades, the Zultys ZIP 47GE is designed to save your business time and money. Dual auto-sensing Gigabit Ethernet ports, with integrated IEEE 802.3af Power-Over-Ethernet (PoE) support, eliminate additional wiring and simplify installation. Zultys' leadership in SIP open standards IP telephony for over 15 years provides peace of mind and investment protection.

## Feature Highlights

- 480x272 pixel color display
- Dual Gigabit Ethernet ports
- Full call control via ZAC
- 27 programmable LCD-labeled keys
- Four context-sensitive soft keys
- Local three-way conference
- Dedicated headset port with EHS support
- Supports ZIP 450M LCD Expansion
- Busy Lamp Field (BLF)
- Built-in Bluetooth and Wi-Fi support
- XML Browser
- XML- and LDAP-based contact directories
- Call forward/Call waiting
- One-touch call transfer and conference
- One-touch call record button with look back capabilities
- Call park and pickup
- Displays caller and called line info
- Call Log and Redial
- Missed call notification
- Paging and Intercom auto-answer
- VLAN, DSCP and QOS support
- SIP open standard
- MXnetwork Redundancy support
- 802.3af Power-over-Ethernet
- Hearing Aid Compatible (HAC) handset
- Log into Call Groups from phone
- Wall mountable (optional bracket required)

View  
ZIP 47GE  
Video



## Feature Keys

- 27 programmable LCD-labeled soft keys
- Four context sensitive soft keys
- Up to ten line keys
- Four navigation keys, select and cancel
- Ten dedicated function keys including: Transfer, Hold, Redial, Mute, Volume, Speakerphone, Headset and Voice Mail

## Audio and Codecs

- Full-duplex speakerphone
- USB headset support (compatible wireless or wired headset required)
- Hearing Aid Compatible (HAC) handset
- Bluetooth headset support (compatible headset required)
- Dedicated RJ9 modular headset port
- Electronic Hook Switch (EHS) support. Requires compatible wireless headset and EHS 4xi adapter (Part: 90-09304)
- G.711  $\mu$ -law / A-law, G.729a
- G.722 wideband
- Independent volume setting for handset, headset, handsfree, and ringer
- Echo cancellation
- Comfort noise
- Packet loss concealment

## Display and Indicators

- 4.3", 480x272 pixel color display
- LED's for message waiting indication (MWI), headset, handsfree, & mute

## Security

- User- and administrator-level passwords
- HTTP/S configuration download and web management
- Phone lock with PIN
- Digest Authentication

## Localization

- English, Chinese, French, German, Italian, Polish, Portuguese, Russian, Spanish and Turkish
- Country-specific call progress tones and cadences

## Protocol

- IETF SIP (RFC3261) and associated RFCs
- Supports six SIP accounts

## Networking and Provisioning

- Dual 10/100/1000 Mbps switched Ethernet ports (LAN and PC ports)
- Wi-Fi IEEE802.11a/b/g/n/ac (2.4GHz/5.0GHz) network support
- Support for DHCP options 66, 43, and 176
- Time and date synchronization using SNTP
- Quality of Service (QoS) support – IEEE 802.1 p/Q VLAN and priority tagging, Type of Services (TOS), and Differentiated Services Code Point
- Network Address Translation (NAT) support
- Integrated HTTP/HTTPS server for web administration
- Mass deployment via central provisioning of configuration files: TFTP, HTTP, and HTTPS
- Built-in troubleshooting tools including network packet capture
- RTP support (RFC1889)
- RTP streaming for Paging and Intercom applications
- IEEE 802.1x protocol support
- LLDP-MED support

## Power

- Integrated IEEE 802.3af Power Over Ethernet (PoE) support (class 3)
- Power Consumption: 2.2 - 5.5W
- Optional AC adapter (5V/2A) sold separately

## Package Content

- Zultys ZIP 47GE phone
- Handset and coil cord
- Ethernet cable
- Desktop footstand
- Quick Start Guide

## Physical

- Dimensions (LWD) - 233 x 223 x 186mm (9.2" x 8.8" x 7.3")
- Weight: 1.0kg (35 oz.)
- Operating Conditions

## Operating Conditions:

- Temperature: 0~40°C (+32~104°F)
- Relative Humidity: 10% to 95%, non-condensing
- Storage Temperature: -40°C to 60°C (-40°F to 140°F)

## Certifications

- CE EMC and Safety
- FCC Part 15 Class B
- IC ICES-003 Issue 6
- RCM EMC, Safety and S004
- HAC US and Canada
- RoHS

## Part Number

- 90-0947GE ZIP 47GE phone, POE, no AC adapter

## MX firmware Requirements

- MX Release 16.0.4 or later



## ZIP 450M Expansion Module

### Display and Keys

- 4.3" 272x480 pixel color screen
- 60 programmable keys (three pages x 20 keys)
- Up to three expansion modules may be daisy chained per phone (Phone and system limits apply to the maximum number of BLF keys)

### Power

- Powered from phone when one module connected, two or three modules requires AC adapter (sold separately)
- Power Consumption: 1.5W

### Physical

- Dimensions (WDH) - 197 x 124 x 138mm (7.8" x 4.9" x 5.4")
- Weight - 410g (14.5 oz.)

### Operating Conditions

- Temperature: -10°C to 50°C (14°F to 122°F)
- Relative Humidity: 10% to 95%, non-condensing

### Part Number

- 90-09450 ZIP 450M Expansion Module



**TCSI** of New Jersey, Inc. / 52 Village Court / Hazlet, NJ 07730  
Tel: +1-732-739-9070

**TCSIOFNJ.COM**